

SECTION 4 - REACTIVITY HAZARD DATA

Compatibility (Materials to Avoid)	Conditions To Avoid Open flame, welding arcs, heat
Hazardous Composition Products May occur Will Not Occur	Reactive metals such as aluminum and magnesium. Strong oxidizers. HCl, CO, CO ₂ , small amounts of phosgene and chlorine.
DANGEROUS POLYMERIZATION	Conditions To Avoid None Known

SECTION 5 - HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY	<input checked="" type="checkbox"/> Inhalation	<input type="checkbox"/> Ingestion	<input type="checkbox"/> Not Hazardous
	<input checked="" type="checkbox"/> Skin Absorption	<input type="checkbox"/> Eye	
ACUTE EFFECTS	Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.		
	Eye Contact: Irritation		
	Skin Contact: Defatting of skin		
	Ingestion: Nausea. Possible chemical pneumonitis if aspirated into lungs.		
CHRONIC EFFECTS	(Effects due to excessive exposure to the raw materials of this mixture) May cause cardiac abnormality, liver abnormalities, kidney and/or lung damage.		
Medical Conditions Generally Aggravated by Exposure	May aggravate existing eye, skin, or upper respiratory conditions.		

EMERGENCY FIRST AID PROCEDURES -

Eye Contact	Flush with water for 15 minutes. If irritated, see physician.
Skin Contact	Wash with soap and water. If irritated, see physician.
Inhalation	Remove to fresh air. Resuscitate if necessary. Get medical aid.
Ingestion	Treat symptomatically. Call physician.

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

Respiratory Protection (Specify Type)	If vapor conc. exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor.
Protective Gloves	Neoprene gloves
Eye Protection	Safety glasses recommended
VENTILATION REQUIREMENTS	Adequate ventilation to keep vapor concentration below TLV.
Other Protective Clothing and Equipment	None
Hygienic Work Practices	Wash with soap and water before handling food. Remove contaminated clothing.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE / LEAK PROCEDURES

Steps to be Taken if Material is Spilled Or Released	Absorb with suitable medium. Incinerate or landfill according to local, state, or federal regulations. Do not flush down drains or sewers.
Waste Disposal Methods	Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.
Precautions to be Taken in Handling and Storage	Do not puncture or incinerate containers. Do not store at temperatures above 130°F.
Other Precautions and / or Special Hazards	Avoid food contamination. KEEP OUT OF REACH OF CHILDREN. Avoid breathing vapors.

Information and recommendations contained herein are reliable, but they