



# Garage Door Lube

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 10/17/2014

Revision date: 10/17/2014

Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : Garage Door Lube  
Product code : 128-GDL, 5-GDL, 55-GDL

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Multi-Purpose Lubricant.

#### 1.3. Details of the supplier of the safety data sheet

The Blaster Corporation  
8500 Sweet Valley Drive  
Valley View, Ohio 44125 - USA  
T (216) 901-5800 - F (216) 901-5801  
[www.blasterproducts.com](http://www.blasterproducts.com)

#### 1.4. Emergency telephone number

Emergency number : Chemtrec (800) 424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flammable Liquid 3  
Serious Eye Damage 1  
Aspiration Toxicity 1

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: Flammable liquid and vapour. Causes serious eye damage. May be fatal if swallowed and enters airways.

Precautionary statements (GHS-US)

: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### 2.3. Other hazards

No additional information available.

#### 2.4. Unknown acute toxicity (GHS-US)

4 percent of the mixture consists of ingredient(s) of unknown acute toxicity.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable.

# Garage Door Lube

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### 3.2. Mixture

| Name                                                          | Product identifier  | %       | GHS-US classification       |
|---------------------------------------------------------------|---------------------|---------|-----------------------------|
| Petroleum distillates, hydrotreated light                     | (CAS No) 64742-47-8 | 30 - 60 | Flam. Liq. 3<br>Asp. Tox. 1 |
| Naphtha, petroleum, heavy alkylate                            | (CAS No) 64741-65-7 | 15 - 40 | Flam. Liq. 3<br>Asp. Tox. 1 |
| Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts | (CAS No) 68649-42-3 | 1 - 5   | Skin Irrit. 2<br>Eye Dam. 1 |

\* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Call a physician if irritation develops and persists.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Immediately call a POISON CENTER or doctor/physician.
- First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Immediately call a POISON CENTER or doctor/physician.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory tract irritation.
- Symptoms/injuries after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
- Symptoms/injuries after eye contact : Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

### 4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Dry chemical, carbon dioxide, halons, foam.
- Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon, hydrocarbons.
- Explosion hazard : May form flammable/explosive vapour-air mixture.

### 5.3. Advice for firefighters

- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

### 6.2. Methods and material for containment and cleaning up

- For containment : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Scoop up material and place in a disposal container. Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Provide ventilation.

### 6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

# Garage Door Lube

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from sources of ignition - No smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes. Do not swallow. Handle and open container with care. Use only non-sparking tools. When using do not eat, drink or smoke. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.  
Storage conditions : Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. Store locked up. Keep cool. Keep away from heat, flames and sparks.

#### 7.3. Specific end use(s)

Not available.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

| Petroleum distillates, hydrotreated light (64742-47-8)                     |                |                |
|----------------------------------------------------------------------------|----------------|----------------|
| USA ACGIH                                                                  | ACGIH TWA      | Not available. |
| USA OSHA                                                                   | OSHA PEL (TWA) | Not available. |
| Naphtha, petroleum, heavy alkylate (64741-65-7)                            |                |                |
| USA ACGIH                                                                  | ACGIH TWA      | 100 ppm        |
| USA OSHA                                                                   | OSHA PEL (TWA) | 100 ppm        |
| Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3) |                |                |
| USA ACGIH                                                                  | ACGIH TWA      | Not available. |
| USA OSHA                                                                   | OSHA PEL (TWA) | Not available. |

#### 8.2. Exposure controls

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Hand protection : Wear chemically resistant protective gloves.

Eye protection : Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Environmental exposure controls : Maintain levels below Community environmental protection thresholds.

Other information : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid.

Appearance : Clear.

Colour : Colorless.

Odour : Mild aliphatic.

Odour threshold : No data available.

pH : No data available.

Relative evaporation rate (butylacetate=1) : > 1

Melting point : No data available.

Freezing point : No data available.

Boiling point : 182 °C (360 °F)

Flash point : 54 °C (130 °F) [TCC]

Auto-ignition temperature : No data available.

# Garage Door Lube

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

|                                  |                      |
|----------------------------------|----------------------|
| Decomposition temperature        | : No data available. |
| Flammability (solid, gas)        | : Flammable.         |
| Vapour pressure                  | : No data available. |
| Relative vapour density at 20 °C | : 3.8 (Air=1)        |
| Relative density                 | : 0.81               |
| Solubility                       | : Negligible.        |
| Log Pow                          | : No data available. |
| Log Kow                          | : No data available. |
| Viscosity, kinematic             | : No data available. |
| Viscosity, dynamic               | : No data available. |
| Explosive properties             | : No data available. |
| Oxidising properties             | : No data available. |
| Explosive limits                 | : No data available. |

### 9.2. Other information

No additional information available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2. Chemical stability

Stable under normal storage conditions. May form flammable/explosive vapour-air mixture.

### 10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

### 10.4. Conditions to avoid

Heat. Incompatible materials. Sources of ignition. Excessive water.

### 10.5. Incompatible materials

Strong oxidizing agents, strong reducing agents.

### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon, hydrocarbons.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified.

| Garage Door Lube                                       |                    |
|--------------------------------------------------------|--------------------|
| LD50 oral rat                                          | > 2000 mg/kg       |
| LD50 dermal rabbit                                     | > 2000 mg/kg       |
| LC50 inhalation rat                                    | No data available. |
| Petroleum distillates, hydrotreated light (64742-47-8) |                    |
| LD50 oral rat                                          | > 5000 mg/kg       |
| LD50 dermal rabbit                                     | > 2000 mg/kg       |
| LC50 inhalation rat                                    | > 5.2 mg/l/4h      |
| Naphtha, petroleum, heavy alkylate (64741-65-7)        |                    |
| LD50 oral rat                                          | > 7000 mg/kg       |
| LD50 dermal rabbit                                     | > 2000 mg/kg       |
| LC50 inhalation rat                                    | > 5.04 mg/l/4h     |

|                                   |                                                                     |
|-----------------------------------|---------------------------------------------------------------------|
| Skin corrosion/irritation         | : Based on available data, the classification criteria are not met. |
| Serious eye damage/irritation     | : Causes serious eye damage.                                        |
| Respiratory or skin sensitisation | : Based on available data, the classification criteria are not met. |
| Germ cell mutagenicity            | : Based on available data, the classification criteria are not met. |
| Carcinogenicity                   | : Based on available data, the classification criteria are not met. |
| Reproductive toxicity             | : Based on available data, the classification criteria are not met. |

# Garage Door Lube

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

|                                                    |                                                                                                                                                                                  |
|----------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Specific target organ toxicity (single exposure)   | : Based on available data, the classification criteria are not met.                                                                                                              |
| Specific target organ toxicity (repeated exposure) | : Based on available data, the classification criteria are not met.                                                                                                              |
| Aspiration hazard                                  | : May be fatal if swallowed and enters airways.                                                                                                                                  |
| Symptoms/injuries after inhalation                 | : May cause respiratory tract irritation.                                                                                                                                        |
| Symptoms/injuries after skin contact               | : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.                                                                           |
| Symptoms/injuries after eye contact                | : Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns. |
| Symptoms/injuries after ingestion                  | : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.     |

## SECTION 12: Ecological information

### 12.1. Toxicity

|                   |                                                                   |
|-------------------|-------------------------------------------------------------------|
| Ecology - general | : May cause long-term adverse effects in the aquatic environment. |
|-------------------|-------------------------------------------------------------------|

### 12.2. Persistence and degradability

| Garage Door Lube              |                  |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |

### 12.3. Bioaccumulative potential

| Garage Door Lube          |                  |
|---------------------------|------------------|
| Bioaccumulative potential | Not established. |

### 12.4. Mobility in soil

No additional information available.

### 12.5. Other adverse effects

|                              |                                                      |
|------------------------------|------------------------------------------------------|
| Effect on ozone layer        | : No additional information available.               |
| Effect on the global warming | : No known ecological damage caused by this product. |

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

|                                |                                                                                                                                                                                         |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Waste disposal recommendations | : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible. |
| Additional information         | : Handle empty containers with care because residual vapours are flammable.                                                                                                             |

## SECTION 14: Transport information


In accordance with DOT

### 14.1. UN number

|             |        |
|-------------|--------|
| UN-No.(DOT) | UN1268 |
|-------------|--------|

### 14.2. UN proper shipping name

|                                                   |                                                    |
|---------------------------------------------------|----------------------------------------------------|
| Proper Shipping Name (DOT)                        | : Petroleum distillates, n.o.s. limited quantities |
| Department of Transportation (DOT) Hazard Classes | : 3                                                |
| Hazard labels (DOT)                               | :                                                  |



|                     |       |
|---------------------|-------|
| Packing group (DOT) | : III |
|---------------------|-------|

### 14.3. Additional information

|                               |                                                                             |
|-------------------------------|-----------------------------------------------------------------------------|
| Other information             | : No supplementary information available.                                   |
| Special transport precautions | : Do not handle until all safety precautions have been read and understood. |

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

# Garage Door Lube

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### 15.2. US State regulations

| Garage Door Lube           |                                                                                                                                      |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| State or local regulations | This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm. |

### SECTION 16: Other information

|                       |              |
|-----------------------|--------------|
| Indication of changes | : None.      |
| Date of issue         | : 10/17/2014 |
| Other information     | : None.      |

*Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.*