



FORT ATKINSON, WI 53538-0901
MODESTO, CA 95356-9318
1-800-558-9595

IMPORTANT

MATERIAL SAFETY DATA SHEET

READ CAREFULLY BEFORE USING CHEMICAL

OSHA requires that this form be kept on file.

Product No. KM 603 M

Product Name ETHYL ALCOHOL,
DENATURED 95%

24 HOUR EMERGENCY ASSISTANCE

CHEMTREC 800-424-9300
HAZARD RATING

4-EXTREME
3-SEVERE
2-MODERATE
1-SLIGHT
0-MINIMAL

Health Hazard 2
Flammability 3
Reactivity 0

SECTION I NAME

Chemical Synonyms	Proprietary Solvent
Formula	C ₂ H ₅ OH
C.A.S. No.	64-17-5

SECTION II HAZARDOUS INGREDIENTS OF MIXTURES

Principal Hazardous Component(s)	%	P.E.L.	TLV Units
Ethyl Alcohol (190pf) CAS# 64-17-5	92.47	1000 ppm	1000 ppm (TWA)
Methyl Alcohol* CAS# 67-56-1	3.70	200 ppm	200 ppm (TWA)
Methyl Isobutyl Ketone* CAS# 108-10-1	1.89	100 ppm	50 ppm(TWA)
Ethyl Acetate CAS# 141-78-6	1.94	400 ppm	400 ppm (TWA)
Petroleum Naphtha* CAS# 64742-89-8	.97	500 ppm	400 ppm (TWA)

* chemical subject to the reporting requirements of SARA Title III.

SECTION III PHYSICAL DATA

Melting Point (°F)	-114°C (-173°F)	Specific Gravity (H ₂ O=1)	0.7900
Boiling Point (°F)	80°C (176°F)	Percent Volatile by Volume (%)	100%
Vapor Pressure (mm Hg)	59.3 @ 25°C	Evaporation Rate (Butyl Acetate = 1)	3.3
Vapor Density (Air=1)	1.6		
Solubility in Water	100%		
Appearance & Odor	Clear colorless liquid, mild odor		

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used)	63°F (17°C) closed cup	Flammable Limits in Air % by Volume	Lower 3.3	Upper 19.0
Extinguisher Media	Water spray, dry chemical, foam or carbon dioxide. Water spray may be used to keep fire exposed containers cool.			

Special Firefighting Procedures

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

Unusual Fire and Explosion Hazards

Flammable! Autoignition temperature 363°C (685°F). Above flash point, vapor-air mixtures are explosive within flammable limits noted above. Vapors can flow along surfaces to distant ignition source and flash back.

D.O.T. Ethanol, 3, UN1170, PGII

Approved by the U.S. Department of Labor "essentially similar" to form OSHA-20

SECTION V HEALTH HAZARD DATA

Threshold Limit Value

See Section II

Effects of Overexposure

Toxic due to denaturants. Acute: Irritation to eyes, skin, lungs and GI tract. Narcosis, nausea, vision impairment. Chronic: Dermatitis. Blindness due to presence of methanol. Kidney and liver damage.

Emergency and First Aid Procedures

Skin: Remove any contaminated clothing. Wash skin with soap and water from at least 15 minutes. Get medical attention if irritation develops or persists. **Eyes:** Wash eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately. **Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician. **Ingestion:** If swallowed, induce vomiting immediately by giving two glasses of water and sticking finger down throat. Never give anything by mouth to an unconscious person. Call a physician immediately.

SECTION VI REACTIVITY DATA

Stability	Conditions to Avoid
Stable ☒ Unstable ☐	Avoid heat and ignition sources.
Incompatibility (Materials to Avoid)	Strong oxidants, silver salts, halogen halides, alkali metals, metal hydrides.
Hazardous Decomposition Products	Carbon oxides.
Hazardous Polymerization	Conditions to Avoid
May Occur ☐ Will Not Occur ☒	None

SECTION VII SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled

Ventilate area of leak or spill. Remove all sources of ignition. Cleanup personnel require protective clothing and respiratory protection from vapors. Small spills may be absorbed on paper towels and evaporated in a fume hood. Large spills: Contain and recover liquid when possible or absorb with vermiculite, dry sand, earth or similar material. Scoop up with non-sparking tool and place in a closed container.

Waste Disposal Method

Discharge, treatment, or disposal may be subject to Federal, State or Local laws. These disposal guidelines are intended for the disposal of catalog-size quantities only.

Dispose of in accordance with all applicable Federal, state and local regulations.

SECTION VIII SPECIAL PROTECTION INFORMATION

Respiration Protection Organic cartridge or self-contained.
(Specify Type)

Ventilation	Local Exhaust ☒ (recommended)	Special ☐
	Mechanical (General) ☒ (preferred)	Other ☐
Protective Gloves	Appropriate chemical resistant gloves	Eye Protection Goggles
Other Protective Equipment	Lab coat. Eye wash station and safety shower.	

SECTION IX SPECIAL PRECAUTIONS

Precautions to be Taken in Handling & Storing

Keep container tightly closed when not in use.

Store in a cool well ventilated location.

Other Precautions

Read label on container before using. Do not wear contact lenses when working with chemicals.

Conditions Aggravated/Target Organs: Persons with skin, eye, respiratory or kidney/liver disorders may be more susceptible. Liver/Kidney.

Approved by Steven C. Quandt

Effective Date 4/5/2005

For laboratory use only. Not for drug, food or household use. Keep out of reach of children.

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to the other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees.