

00618-2014
-2015Material Safety Data Sheet

Product Name:
LIQUITEX[®] ACRYLIC GLAZING MEDIUM

Product Family:

1. Chemical Product and Company Identification

Colart Americas, Inc.
11 Constitution Avenue
PO Box 1396
Piscataway, NJ 08855
1-800-445-4278

EMERGENCY TELEPHONE NUMBER:
1-800-628-3385

PRODUCT USE:
Arts and Crafts

CREATION DATE:
25 September 2002

REVISION DATE:
18 August 2006

2. Composition, Information on Ingredients

COMPONENT
Product has been certified as non-toxic by The Art and Creative
Materials Institute, Inc. and conforms to ASTM D-4236 Standard Practice for
Labeling Art Materials for Acute and Chronic Adverse Health Hazards.
CAS NUMBER: Not assigned.
EC NUMBER: Not assigned.
PERCENTAGE: 100.0

3. Hazards Identification

None

EC CLASSIFICATION (CALCULATED):
Not classified.

EMERGENCY OVERVIEW:

COLOR
Translucent white

PHYSICAL FORM:
liquid

ODOR:
fruity odor

MAJOR HEALTH HAZARDS:
No significant target effects reported

POTENTIAL HEALTH EFFECTS:

INHALATION:
none

SKIN CONTACT:
none

LIQUITEX(R) ACRYLIC GLAZING MEDIUM

Page 1

21-08/2006

EYE CONTACT:
none

INGESTION:
none

CARCINOGEN STATUS:

OSHA:
No

NTP:
No

IARC:
No

4. First Aid Measures

INHALATION:
It is unlikely that emergency treatment will be required. Remove from exposure. Get medical attention, if needed.

SKIN CONTACT:
It is unlikely that emergency treatment will be required. If adverse effects occur, wash with soap or mild detergent and large amounts of water. Get medical attention, if needed.

EYE CONTACT:
It is unlikely that emergency treatment will be required. Wash with large amounts of water or normal saline until no evidence of chemical remains (at least 15-20 minutes). Get medical attention immediately.

INGESTION:
Contact local poison control center or physician immediately.

5. Fire Fighting Measures

FIRE AND EXPLOSION HAZARDS:
Slight fire hazard.

EXTINGUISHING MEDIA:
carbon dioxide, regular dry chemical, regular foam, water

FIRE FIGHTING:
Move container from fire area if it can be done without risk. Avoid inhalation of material or combustion by-products.

FLASH POINT:
No data available.

6. Accidental Release Measures

OCCUPATIONAL RELEASE:
Absorb with sand or other non-combustible material. Collect spilled material in appropriate container for disposal.

7. Handling and Storage
Store and handle in accordance with all current regulations and standards. See original container for storage recommendations. Keep separated from incompatible substances.

8. Exposure Controls, Personal Protection**EXPOSURE LIMITS:**

LIQUITEX(R) ACRYLIC GLOSS MEDIUM AND VARNISH:
No occupational exposure limits established.

VENTILATION:

Based on available information, additional ventilation is not required.

EYE PROTECTION:

Eye protection not required under normal conditions.

CLOTHING:

Protective clothing is not required under normal conditions.

GLOVES:

Wear appropriate chemical resistant gloves.

PROTECTIVE MATERIAL TYPES:

neoprene, rubber

RESPIRATOR:

No respirator is required under normal conditions of use.
Under conditions of frequent use or heavy exposure, respiratory protection may be needed.

9. Physical and Chemical Properties**PHYSICAL STATE:**

liquid

COLOR:

white

ODOR:

fruity odor

BOILING POINT:

> 100 C

FREEZING POINT:

Not available

VAPOR PRESSURE:

Not available

VAPOR DENSITY: Air = 1

> 1

SPECIFIC GRAVITY:

1.1

WATER SOLUBILITY:

Miscible

PH:

8-9

VOLATILITY:

Not available

ODOR THRESHOLD:

Not available

EVAPORATION RATE: BuAc = 1

< 1

LIQUITEX(R) ACRYLIC GLAZING MEDIUM

Page 3

21/08/2006

10. Stability and Reactivity**REACTIVITY:**

Stable at normal temperatures and pressure.

CONDITIONS TO AVOID:

None reported.

INCOMPATIBILITIES:

oxidizing materials

HAZARDOUS DECOMPOSITION:

Thermal decomposition products:
oxides of carbon

POLYMERIZATION:

Will not polymerize.

11. Toxicological Information

Not available

12. Ecological Information

Not available

13. Disposal Considerations

Dispose in accordance with all applicable regulations.

14. Transport Information

No classification assigned.

LAND TRANSPORT ADR/RID:

No classification assigned.

AIR TRANSPORT IATA/ICAO:

No classification assigned.

MARITIME TRANSPORT IMDG:

No classification assigned.

15. Regulatory Information**U.S. REGULATIONS:****TSCA INVENTORY STATUS:**

Y

TSCA 12(b) EXPORT NOTIFICATION:

Not listed.

CERCLA SECTION 103 (40CFR302.4):

N

SARA SECTION 302 (40CFR355.30):

N

SARA SECTION 304 (40CFR355.40):

N

SARA SECTION 313 (40CFR372.65):

N

SARA HAZARD CATEGORIES, SARA SECTIONS 311/312 (40CFR370.21):**ACUTE:**

N

LIQUITEX(R) ACRYLIC GLAZING MEDIUM

Page 4

21/08/2006

CHRONIC:

N

FIRE:

N

REACTIVE:

N

SUDDEN RELEASE:

N

OSHA PROCESS SAFETY (29CFR1910.119):

N

STATE REGULATIONS:

California Proposition 65:

N

EUROPEAN REGULATIONS:

EC NUMBER:

Not assigned.

16. Other Information

The information contained herein is provided for identification of hazards in normal use and does not constitute a product specification.

